



# Sword Track 48V



## 5 / Product Color / Ürün Renk




## 4 / Angle / Açısı



\* See page 246 for ldt files. / Işık eğrileri için sayfa 246 bakınız.

## Technical Drawing / Teknik Çizim



### EN

- Extruded aluminium body.
- 48V DC Voltage Input.
- Clever thermal design with passive heat dissipation.
- With DC/DC in-track adaptor compatible to Stucchi Low-Voltage track system. .
- Opal diffuser.
- Suitable for DALI DIM and 1-10V system.
- High tech control systems of Warm Dim and Wireless Dim options.
- Basic colours: White, Black, Gray, Dark Gray, RAL9010 and special color options.
- High CRI>90 and standart CRI>80 LED options available.
- High colour consistency: <3 SDCM

### TR

- Alüminyum profil gövde.
- 48V DC girişli.
- Pasif soğutma teknolojisine sahip akıllı soğutma tasarımı.
- Stucchi 48V ray sistemine uygun DC/DC trafo adaptörlü
- Opal Difüzörlü
- DALI ve 1-10V DIM seçeneği mevcut.
- Yüksek teknoloji kontrol sistemleri olan Kablosuz DIM ve Sıcak DIM uygulamaları yapılabilir.
- Standart renk seçenekleri: Beyaz, Siyah, Gri, Koyu Gri, RAL9010 yanında isteğe bağlı özel renk seçenekleri uygulanabilir.
- Yüksek CRI>90 ve standart CRI>80 LED seçenekleri mevcuttur.
- Yüksek renk uyumu: <3 SDCM

# Sword Track 48V

## Sword Track 48V / I02.LL.15105

Power / Güç	CRI	Order Code / Sipariş Kodu	Kelvin	Lümen T <sub>C</sub> =50° Lümen
15W	CRI>80	I02.LL.15105.(.)...(.)...(.)...(.)...	2700K	1084
			3000K	1118
			4000K	1151
			5000K	1185
15W	CRI>90	I02.LL.15105.(.)...(.)...(.)...(.)...	2700K	1008
			3000K	1039
			4000K	1070
			5000K	1102

\* Code example / Kod örneği:

I02.LL.15105.15.827.WF.01.840  
 1 2 3 4 5 6

- 1- Product code / Armatür kodu
- 2- Power / Güç
- 3- CRI / Kelvin
- 4- Reflector angle / Reflektör açısı
- 5- Colour / Ürün renk
- 6- Length / Uzunluk

## Sword Track 48V / I02.LL.15105

Power / Güç	CRI	Order Code / Sipariş Kodu	Kelvin	Lümen T <sub>C</sub> =50° Lümen
10W	CRI>80	I02.LL.15105.(.)...(.)...(.)...(.)...	2700K	723
			3000K	745
			4000K	767
			5000K	790
10W	CRI>90	I02.LL.15105.(.)...(.)...(.)...(.)...	2700K	672
			3000K	692
			4000K	714
			5000K	735

\* Code example / Kod örneği:

I02.LL.15105.10.827.WF.01.560  
 1 2 3 4 5 6

- 1- Product code / Armatür kodu
- 2- Power / Güç
- 3- CRI / Kelvin
- 4- Reflector angle / Reflektör açısı
- 5- Colour / Ürün renk
- 6- Length / Uzunluk








## Sword Track 48V / I02.LL.15105

Power / Güç	CRI	Order Code / Sipariş Kodu	Kelvin	Lümen T <sub>C</sub> =50° Lümen
5W	CRI>80	I02.LL.15105.(.)...(.)...(.)...(.)...	2700K	361
			3000K	372
			4000K	383
			5000K	395
5W	CRI>90	I02.LL.15105.(.)...(.)...(.)...(.)...	2700K	336
			3000K	346
			4000K	357
			5000K	367

\* Code example / Kod örneği:

I02.LL.15105.5.827.WF.01.280  
 1 2 3 4 5 6

- 1- Product code / Armatür kodu
- 2- Power / Güç
- 3- CRI / Kelvin
- 4- Reflector angle / Reflektör açısı
- 5- Colour / Ürün renk
- 6- Length / Uzunluk

2	Watt - Driving Current / Watt - Sürüş Akımı	3		4	Reflector Angle / Reflektör Açısı	5		6				
		CRI / Kelvin				Product Color / Ürün Renk			Length / Uzunluk			
15	15W - 350mA	827	CRI>80 - 2700K	927	CRI>90 - 2700K		WF	110° - Wide Flood		01	white	840mm
10	10W - 350mA	830	CRI>80 - 3000K	930	CRI>90 - 3000K					02	ral 9010	560mm
5	5W - 350mA	840	CRI>80 - 4000K	940	CRI>90 - 4000K					03	black	280mm
		850	CRI>80 - 5000K	950	CRI>90 - 5000K					04	gray	
										05	dark gray	
										06	special color	