

# Narrow Surface Mounted

## Narrow Surface Mounted / I02.LL.19181



\* Code example / Kod örneği:

I02.LL.19181 . 1135 . 034 . 830 . 01

- 1- Product code / Armatür kodu
- 2- Length / Uzunluk
- 3- Power / Güç
- 4- CRI / Kelvin
- 5- Colour / Ürün renk
- 6- Control type / Kontrol tipi

### Surface Mounting Profile

Sıvaüstü Montaj Profili



Lenght / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	20W 250mA lm	27W 350mA lm
855mm	CRI>80	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	1669	2252
			3000K	1722	2324
			3500K	1749	2360
			4000K	1816	2450
			5000K	1842	2486
855mm	CRI>90	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	1402	1891
			3000K	1442	1945
			3500K	1468	1981
			4000K	1522	2053
Lenght / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	24W 250mA lm	34W 350mA lm
1135mm	CRI>80	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	2029	2866
			3000K	2094	2957
			3500K	2127	3003
			4000K	2208	3118
			5000K	2240	3163
1135mm	CRI>90	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	1705	2406
			3000K	1753	2475
			3500K	1785	2521
			4000K	1851	2612
Lenght / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	30W 250mA lm	43W 350mA lm
1415mm	CRI>80	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	2592	3693
			3000K	2674	3811
			3500K	2716	3870
			4000K	2820	4018
			5000K	2860	4077
1415mm	CRI>90	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	2177	3101
			3000K	2239	3189
			3500K	2280	3248
			4000K	2364	3367
Lenght / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	36W 250mA lm	51W 350mA lm
1695mm	CRI>80	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	3176	4506
			3000K	3277	4651
			3500K	3329	4723
			4000K	3456	4903
			5000K	3506	4975
1695mm	CRI>90	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	2668	3784
			3000K	2744	3892
			3500K	2794	3964
			4000K	2897	4108
Lenght / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	42W 250mA lm	59W 350mA lm
1975mm	CRI>80	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	3783	5333
			3000K	3903	5504
			3500K	3964	5589
			4000K	4116	5802
			5000K	4175	5888
1975mm	CRI>90	I02.LL.19181 . (...) . (...) . (...) . (...)	2700K	3178	4478
			3000K	3268	4606
			3500K	3327	4692
			4000K	3456	4862

2	Lenght / Uzunluk (A)	3	Watt - Driving Current / Watt - Sürüş Akımı		4		CRI / Kelvin	5			
			20W	27W	24W	34W		827	927	01	white
	855mm		20W (Direct) - 250mA	27W (Direct) - 350mA	827	927	CRI>80 - 2700K	927	CRI>90 - 2700K	01	white
	1135mm		24W (Direct) - 250mA	34W (Direct) - 350mA	830	930	CRI>80 - 3000K	930	CRI>90 - 3000K	02	ral 9010
	1415mm		30W (Direct) - 250mA	43W (Direct) - 350mA	835	935	CRI>80 - 3500K	935	CRI>90 - 3500K	03	black
	1695mm		36W (Direct) - 250mA	51W (Direct) - 350mA	840	940	CRI>80 - 4000K	940	CRI>90 - 4000K	04	gray
	1975mm		42W (Direct) - 250mA	59W (Direct) - 350mA	850		CRI>80 - 5000K			05	dark gray
										06	special color