

# Narrow Track Mounted

## Narrow Track Montend / 102.LL.19187



\* Code example / Kod örneği:

102.LL.19187 . 1150 . 033 . 100 . 830 . 01  
 1 2 3 4 5 6

- 1- Product code / Armatür kodu
- 2- Length / Uzunluk
- 3- Power / Güç
- 4- Beam Angle / Işık Açısı
- 5- CRI / Kelvin
- 6- Colour / Ürün renk
- 7- Control type / Kontrol tipi

### Track Adaptor

Ray Soketi



Length / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	20W 250mA lm	25W 350mA lm
870mm	CRI>80	102.LL.19187 . (...) . (...) . (...) . (...)	2700K	1763	2368
			3000K	1820	2444
			3500K	1848	2482
			4000K	1919	2557
			5000K	1947	2615
870mm	CRI>90	102.LL.19187 . (...) . (...) . (...) . (...)	2700K	1481	1989
			3000K	1524	2046
			3500K	1497	2084
			4000K	1608	2160
			4000K	1608	2160
Length / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	24W 250mA lm	33W 350mA lm
1150mm	CRI>80	102.LL.19187 . (...) . (...) . (...) . (...)	2700K	2145	3014
			3000K	2214	3111
			3500K	2248	3159
			4000K	2334	3280
			5000K	2368	3328
1150mm	CRI>90	102.LL.19187 . (...) . (...) . (...) . (...)	2700K	1802	2532
			3000K	1853	2512
			3500K	1887	2653
			4000K	1956	2749
			4000K	1956	2749
Length / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	30W 250mA lm	43W 350mA lm
1430mm	CRI>80	102.LL.19187 . (...) . (...) . (...) . (...)	2700K	2740	3886
			3000K	2827	4010
			3500K	2871	4072
			4000K	2981	4228
			5000K	3025	4290
1430mm	CRI>90	102.LL.19187 . (...) . (...) . (...) . (...)	2700K	2301	3264
			3000K	2367	3357
			3500K	2411	3420
			4000K	2498	3544
			4000K	2498	3544
Length / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	36W 250mA lm	51W 350mA lm
1710mm	CRI>80	102.LL.19187 . (...) . (...) . (...) . (...)	2700K	3358	4742
			3000K	3466	4893
			3500K	3519	4793
			4000K	3654	5159
			5000K	3708	5235
1710mm	CRI>90	102.LL.19187 . (...) . (...) . (...) . (...)	2700K	2821	3983
			3000K	2902	4097
			3500K	2850	4173
			4000K	3063	4324
			4000K	3063	4324

2	Length / Uzunluk (A)	3	Watt - Driving Current / Watt - Sürüş Akımı	4	Beam Angle / Işık Açısı	5		6	Product Color / Ürün Renk	
						CRI / Kelvin				
870mm	20W 25W	20W (Direct) - 250mA 25W (Direct) - 350mA	WF	100° - Wide Flood	827	CRI>80 - 2700K	927	CRI>90 - 2700K	01	white
									02	ral 9010
1150mm	24W 33W	24W (Direct) - 250mA 33W (Direct) - 350mA	D.ASY.	Double Asymmetric	830	CRI>80 - 3000K	930	CRI>90 - 3000K	03	black
									04	gray
1430mm	30W 43W	30W (Direct) - 250mA 43W (Direct) - 350mA			835	CRI>80 - 3500K	935	CRI>90 - 3500K	05	dark gray
									06	special color
1710mm	36W 51W	36W (Direct) - 250mA 51W (Direct) - 350mA			840	CRI>80 - 4000K	940	CRI>90 - 4000K		
					850	CRI>80 - 5000K				