

Narrow Track Mounted

Narrow Track Mounted / 102.LL.19287



* Code example / Kod örneği:

102.LL.19287 . 1140 . 056 . 060 . 830 . 01

- 1- Product code / Armatür kodu
- 2- Length / Uzunluk
- 3- Power / Güç
- 4- Beam Angle / Işık Açısı
- 5- CRI / Kelvin
- 6- Colour / Ürün renk
- 7- Control type / Kontrol tipi

Track Adaptor

Ray Soketi



Length / Uzunluk (A)	CRI	Order Code / Sipariş Kodu	Kelvin	19.5W 250mA lm	27W 350mA lm	39W 500mA lm	56W 700mA lm
1140mm	CRI>80	102.LL.19287 . (...) . (...) . (...)	2700K	2179	2974	4116	5343
			3000K	2249	3069	4247	5691
			3500K	2283	3117	4313	5779
			4000K	2371	3236	4478	6000
	CRI>90	102.LL.19287 . (...) . (...) . (...)	2700K	2406	3283	4544	6088
			3000K	1830	2498	3457	4632
			3500K	1883	2570	3556	4765
			4000K	1917	2617	3622	4853
1700mm	CRI>80	102.LL.19287 . (...) . (...) . (...)	2700K	2406	3283	4544	6088
			3000K	1830	2498	3457	4632
			3500K	1883	2570	3556	4765
			4000K	1917	2617	3622	4853
	CRI>90	102.LL.19287 . (...) . (...) . (...)	2700K	1987	2712	3753	5029
			3000K	3211	4378	6067	8125
			3500K	3314	4518	6261	8385
			4000K	3365	4588	6358	8515
2260mm	CRI>80	102.LL.19287 . (...) . (...) . (...)	2700K	3494	4763	6601	8840
			3000K	3545	4833	6698	8970
			3500K	2697	3677	5096	6825
			4000K	2774	3782	5242	7020
	CRI>90	102.LL.19287 . (...) . (...) . (...)	2700K	2826	3852	5339	7150
			3000K	2929	3992	5533	7410
			3500K	4356	5937	8228	11020
			4000K	4495	6127	8491	11372
2260mm	CRI>80	102.LL.19287 . (...) . (...) . (...)	3500K	4565	6221	8623	11549
			4000K	4739	6459	8952	11989
			5000K	4809	6554	9084	12166
			2700K	3658	4986	6911	9256
	CRI>90	102.LL.19287 . (...) . (...) . (...)	3000K	3763	5129	7109	9521
			3500K	3833	5224	7241	9697
			4000K	3972	5414	7504	10050

Complete Code / Komple Kod	2	3	4	5		6		
	Length / Uzunluk (A)	Watt - Driving Current / Watt - Sürüş Akımı	Beam Angle / Işık Açısı	CRI / Kelvin		Product Color / Ürün Renk		
	1140mm	19.5W	19.5W (Direct) - 250mA	ME	30° - Medium	827 CRI>80 - 2700K	927 CRI>90 - 2700K	01 white
		27W	27W (Direct) - 350mA	FL	60° - Flood	830 CRI>80 - 3000K	930 CRI>90 - 3000K	02 ral 9010
		39W	39W (Direct) - 500mA	WF	90° - Wide Flood	835 CRI>80 - 3500K	935 CRI>90 - 3500K	03 black
		56W	56W (Direct) - 700mA					04 gray
	1700mm	29W	29W (Direct) - 250mA	S.ASY.	Single Asymmetric	840 CRI>80 - 4000K	940 CRI>90 - 4000K	05 dark gray
		41W	41W (Direct) - 350mA					06 special color
		58W	58W (Direct) - 500mA	D.ASY.	Double Asymmetric	850 CRI>80 - 5000K		
		82W	82W (Direct) - 700mA					
	2260mm	39W	39W (Direct) - 250mA					
		51W	51W (Direct) - 350mA					
		78W	78W (Direct) - 500mA					
		109W	109W (Direct) - 700mA					