



- Aluminium body.
- Microprismatic PMMA opal diffuser.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V, DALI and switch dimming options available upon request.
- Over 110lm/W efficiency.
- Emergency kit system can be integrated.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- 24V DC Electronic Led driver positioned inside luminaire.
- Steel suspension cord with up to 5mt lenght option.

- Alüminyum gövde.
- Mikroprizmatik PMMA opal difüzörlü.
- 220-240V / 50-60Hz enerji giriřli.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- 110lm/W'in üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bađlı özel renk seçenekleri mevcuttur.
- 24V DC Led trafosu armatürün içindedir.
- 5mt uzunluk seçeneđine kadar tercih edilebilir çelik sarkit tel.

### Sivo / I02.LL.13128.45

|   |                 |      |
|---|-----------------|------|
| Order Code / Ürün Kodu                                  | I02.LL.13128.45 |      |
| LED   | SMD LED         |      |
| Led Power / Led Gücü                                    | 23W             |      |
| System Power / Sistem Gücü                              | 25W             |      |
| Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80 | 2700K           | 2375 |
|   | 3000K           | 2450 |
|   | 3500K           | 2500 |
|   | 4000K           | 2550 |
|   | 5000K           | 2625 |
| Product Diameter / Ürün Çapı (A)                        | Ø450mm          |      |
| Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu     | ✓               |      |
| 1-10V Dimming Option / 1-10V Dim Seçeneđi               | ✓               |      |
| Dali Dimming Option / Dali Dim Seçeneđi                 | ✓               |      |

Suspension Cord  
Ray Sarkıtma Teli

